В	Sektion	PERFORMING OPERATIONS; TRANSPORTING
B67	Klasse	OPENING OR CLOSING BOTTLES, JARS OR SIMILAR CONTAINERS; LIQUID HANDLING
B67B	Unterklasse	APPLYING CLOSURE MEMBERS TO BOTTLES, JARS, OR SIMILAR CONTAINERS; OPENING CLOSED CONTAINERS (opening or closing devices attached to, or incorporated in, containers or container closures B65D)
B67B 1/00	Hauptgruppe	Closing bottles, jars, or similar containers by applying stoppers (stoppers per seB65D 39/00) [1,
		2006.01]
B67B 1/03	1-Punkt Untergruppe	. Pretreatment of stoppers, e.g. cleaning, steaming, heating, impregnating or coating; Applying resilient rings to stoppers (mechanical working of cork B27J 5/00) [5, 2006.01]
B67B 1/04	1-Punkt Untergruppe	. by inserting threadless stoppers, e.g. corks [1, 2006.01]
B67B 1/06	1-Punkt Untergruppe	. by inserting and rotating screw stoppers [1, 2006.01]
B67B 1/08	1-Punkt Untergruppe	. Securing stoppers, e.g. swing stoppers, which are held in position by associated pressure-applying means coacting with the bottle neck [1, 2006.01]
B67B 1/10	1-Punkt Untergruppe	. by inserting disc closures [6, 2006.01]
B67B 3/00	Hauptgruppe	Closing bottles, jars, or similar containers by applying caps (caps per seB65D 41/00) [1, 2006.01]
B67B 3/02	1-Punkt Untergruppe	. by applying flanged caps, e.g. crown caps, and securing by deformation of flanges [1, 2006.01]
B67B 3/04	2-Punkt Untergruppe	Cutting caps from strip material in capping machines (devices for registering moving strip material B65H 23/00) [1, 2006.01]
B67B 3/06	2-Punkt Untergruppe	Feeding caps to capping heads [1, 2006.01]
B67B 3/062	3-Punkt Untergruppe	from a magazine [1, 2006.01]
B67B 3/064	3-Punkt Untergruppe	from a hopper [1, 2006.01]
B67B 3/10	2-Punkt Untergruppe	Capping heads for securing caps [1, 2006.01]
B67B 3/12	3-Punkt Untergruppe	characterised by being movable axially relative to cap to deform flanges thereof, e.g. to press projecting flange rims inwardly [1, 2006.01]
B67B 3/14	3-Punkt Untergruppe	characterised by having movable elements, e.g. hinged fingers, for applying radial pressure to the flange of the cap (B67B 3/16, B67B 3/18 take precedence) [1, 5, 2006.01]
B67B 3/16	3-Punkt Untergruppe	characterised by having resilient deforming elements, e.g. resilient sleeves or collars (B67B 3/18 takes precedence) [1, 5, 2006.01]
B67B 3/18	3-Punkt Untergruppe	characterised by being rotatable, e.g. for forming screw threads in situ [1, 5, 2006.01]
B67B 3/20	1-Punkt Untergruppe	. by applying and rotating preformed threaded caps (forming threads <u>in situ</u> by resilient deforming means
		B67B 3/16, by rotary capping heads B67B 3/18) [1, 5, 2006.01]
B67B 3/22	1-Punkt Untergruppe	. by applying snap-on caps [1, 2006.01]
B67B 3/24	1-Punkt Untergruppe	. Special measures for applying and securing caps under vacuum [1, 2006.01]
B67B 3/26	1-Punkt Untergruppe	. Applications of control, warning, or safety devices in capping machinery [1, 2006.01]
B67B 3/28	1-Punkt Untergruppe	. Mechanisms for causing relative movement between bottle or jar and capping head [5, 2006.01]
B67B 5/00	Hauptgruppe	Applying protective or decorative covers to closures; Devices for securing bottle closures with

Symbol	Тур	Titel
		wire (infant-feeding teats with means for fastening to bottles A61J 11/04) [1, 6, 2006.01]
B67B 5/03	1-Punkt Untergruppe	. Applying protective or decorative covers to closures, e.g. by forming in situ [3, 2006.01]
B67B 5/05	2-Punkt Untergruppe	by applying liquids, e.g. by dipping [3, 2006.01]
B67B 5/06	1-Punkt Untergruppe	. Devices for securing bottle closures with wire (B67B 1/08 takes precedence) [1, 2006.01]
B67B 6/00	Hauptgruppe	Closing bottles, jars or similar containers by applying closure members, not provided for in groups B67B 1/00-B67B 5/00 [2009.01]
B67B 7/00	Hauptgruppe	Hand- or power-operated devices for opening closed containers (nail pullers or extractors B25C 11/00; attached to, or incorporated in, containers or container closures B65D) [1, 2006.01]
B67B 7/02	1-Punkt Untergruppe	. for removing stoppers [1, 2006.01]
B67B 7/04	2-Punkt Untergruppe	Cork-screws [1, 2006.01]
B67B 7/06	2-Punkt Untergruppe	Other cork removers [1, 2006.01]
B67B 7/08	3-Punkt Untergruppe	using air or gas pressure [1, 2006.01]
B67B 7/10	2-Punkt Untergruppe	with means for retrieving stoppers from the interior of the container [1, 2006.01]
B67B 7/12	1-Punkt Untergruppe	. for removing disc-closures [1, 2006.01]
B67B 7/14	1-Punkt Untergruppe	. for removing tightly-fitting lids or covers, e.g. of shoe-polish tins, by gripping and rotating [1, 2006.01]
B67B 7/15	2-Punkt Untergruppe	finger grapple type [5, 2006.01]
B67B 7/16	1-Punkt Untergruppe	. for removing flanged caps, e.g. crown caps [1, 2006.01]
B67B 7/18	1-Punkt Untergruppe	. for removing threaded caps (B67B 7/14 takes precedence; wrenches B25B 13/00) [1, 2, 2006.01]
B67B 7/20	1-Punkt Untergruppe	. for breaking vacuum seals between lids or covers and bodies of preserving jars, e.g. by wedge action [1, 2006.01]
B67B 7/22	2-Punkt Untergruppe	incorporating loops, e.g. of wire, which are tightened around seal [1, 2006.01]
B67B 7/40	1-Punkt Untergruppe	. Devices for engaging tags, strips, or tongues for opening by tearing, e.g. slotted keys for opening sardine tins [1, 2006.01]
B67B 7/42	1-Punkt Untergruppe	. Devices for removing barrel bungs [1, 2006.01]
B67B 7/44	1-Punkt Untergruppe	. Combination tools, e.g. comprising cork-screws, can piercers, crown-cap removers (combinations of opening devices with cutting tools B26, with devices serving other purposes, <u>see</u> the appropriate places, e.g. B25F, B43K 29/00) [1, 2006.01]
B67B 7/46	1-Punkt Untergruppe	. Cutting devices, i.e. devices including at least one cutting element having one or more cutting edges for piercing through the wall of a closed container, e.g. can openers (B67B 7/44 takes precedence; machines for domestic use with a plurality of interchangeable units A47J 43/06, A47J 44/00; hand-held cutting tools, cutting, severing, in general B26) [4, 2006.01]
B67B 7/48	2-Punkt Untergruppe	punch type, i.e. the cutting element including at least one sharp cutting edge adapted to pierce through the container wall in, ordinarily, a single operating stroke [4, 2006.01]
B67B 7/50	3-Punkt Untergruppe	with fulcrum, i.e. a lever-like actuating handle with provision to establish a pivot point [4, 2006.01]
B67B 7/52	3-Punkt Untergruppe	Plural spaced cutting edges adapted to pierce the container during a single operating stroke [4, 2006.01]
B67B 7/54	2-Punkt Untergruppe	sweep cutter type, i.e. an opening device including means to establish a pivot point between the cutting element and the container and having means to move the cutting element about the pivot point [4, 2006.01]

Symbol	Тур	Titel
B67B 7/56	3-Punkt Untergruppe	with container penetrating pivot and variable cutter radius, i.e. the distance between the cutting element and the penetrating pivot being changeable [4, 2006.01]
B67B 7/58	4-Punkt Untergruppe	Freely slidable cutter [4, 2006.01]
B67B 7/60	2-Punkt Untergruppe	having force multiplying means employed to relatively turn the container and cutting element about a fixed point to force the cutting element to traverse the container [4, 2006.01]
B67B 7/62	2-Punkt Untergruppe	Progressive fulcrum, i.e. having a lever-like actuating handle and provision to establish a pivot point which is progressively translated relative to the container during the opening operation [4, 2006.01]
B67B 7/64	3-Punkt Untergruppe	with guide means to engage container wall and guide the cutting element thereabout [4, 2006.01]
B67B 7/66	3-Punkt Untergruppe	cutter pivoted to reaction member [4, 2006.01]
B67B 7/68	2-Punkt Untergruppe	shear type, i.e. including cutting elements co-operating with one another so that their respective cutting edges move pass and in substantial contact with each other to perform the cutting operation [4, 2006.01]
B67B 7/70	2-Punkt Untergruppe	including an annular, driven, wheel-like roller member adapted to continuously engage a container chime during the opening operation [4, 2006.01]
B67B 7/72	3-Punkt Untergruppe	Cutter comprising rotatable disc [4, 2006.01]
B67B 7/74	3-Punkt Untergruppe	Roller drive means causes initial piercing, i.e. force applied to rotate the wheel-like member causes the cutting element to pierce the container wall [4, 2006.01]
B67B 7/76	3-Punkt Untergruppe	adapted to pierce container side wall [4, 2006.01]
B67B 7/78	2-Punkt Untergruppe	including plural cutters [4, 2006.01]
B67B 7/80	2-Punkt Untergruppe	with means to cover an opening in the container made by the cutting element [4, 2006.01]
B67B 7/82	2-Punkt Untergruppe	with means to prevent the cut portion from dropping into the container or to raise the cut portion out of the container [4, 2006.01]
B67B 7/84	2-Punkt Untergruppe	adapted for right or left-hand operation, i.e. the device is capable of being operated in either direction about the container [4, 2006.01]
B67B 7/86	2-Punkt Untergruppe	with spout or means to deform or bend the material of the container to form a spout [4, 2006.01]
B67B 7/88	2-Punkt Untergruppe	with means to clean or sanitise the cutting element [4, 2006.01]
B67B 7/90	2-Punkt Untergruppe	with sensor, activator and controller [4, 2006.01]
B67B 7/92	1-Punkt Untergruppe	. by breaking, e.g. for ampoules [5, 2006.01]