

| Symbol           | Typ                 | Titel   |
|------------------|---------------------|---|
| <b>F</b>         | <b>Sektion</b>      | <b>MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING</b>   |
| <b>F04</b>       | <b>Klasse</b>       | <b>POSITIVE-DISPLACEMENT MACHINES FOR LIQUIDS; PUMPS FOR LIQUIDS OR ELASTIC FLUIDS</b>  |
| <b>F04C</b>      | <b>Unterklasse</b>  | <b>ROTARY-PISTON, OR OSCILLATING-PISTON, POSITIVE-DISPLACEMENT MACHINES FOR LIQUIDS (engines driven by liquids F03C); ROTARY-PISTON, OR OSCILLATING-PISTON, POSITIVE-DISPLACEMENT PUMPS (engine fuel-injection pumps F02M)</b>  |
|                  |                     | <b><u>Machines for liquids; Pumps for liquids or for liquids and elastic fluids [2011.01]</u></b>   |
| <b>F04C 2/00</b> | <b>Hauptgruppe</b>  | <b>Rotary-piston machines or pumps (with non-parallel axes of co-operating members F04C 3/00; with the working-chamber walls at least partly resiliently deformable F04C 5/00; with fluid ring or the like F04C 7/00; rotary-piston pumps specially adapted for elastic fluids F04C 18/00, F04C 19/00; rotary-piston machines or pumps in which the working-fluid is exclusively displaced by, or exclusively displaces, one or more reciprocating pistons F04B) [3, 2006.01]</b> |
| F04C 2/02        | 1-Punkt Untergruppe | . of arcuate-engagement type, i.e. with circular translatory movement of co-operating members, each member having the same number of teeth or tooth-equivalents [3, 2006.01]  |
| F04C 2/04        | 2-Punkt Untergruppe | . . of internal-axis type [3, 2006.01]  |
| F04C 2/06        | 2-Punkt Untergruppe | . . of other than internal-axis type (F04C 2/063 takes precedence) [3, 2006.01]   |
| F04C 2/063       | 2-Punkt Untergruppe | . . with coaxially-mounted members having continuously-changing circumferential spacing between them [3, 2006.01]   |
| F04C 2/067       | 3-Punkt Untergruppe | . . . having cam-and-follower type drive [3, 2006.01]   |
| F04C 2/07        | 3-Punkt Untergruppe | . . . having crankshaft-and-connecting-rod type drive [3, 2006.01]  |
| F04C 2/073       | 3-Punkt Untergruppe | . . . having pawl-and-ratchet type drive [3, 2006.01]   |
| F04C 2/077       | 3-Punkt Untergruppe | . . . having toothed-gearing type drive [3, 2006.01]  |
| F04C 2/08        | 1-Punkt Untergruppe | . of intermeshing-engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing [3, 2006.01]   |
| F04C 2/10        | 2-Punkt Untergruppe | . . of internal-axis type with the outer member having more teeth or tooth-equivalents, e.g. rollers, than the inner member [3, 2006.01]  |
| F04C 2/107       | 3-Punkt Untergruppe | . . . with helical teeth [3, 2006.01]   |
| F04C 2/113       | 3-Punkt Untergruppe | . . . the inner member carrying rollers intermeshing with the outer member [3, 2006.01]   |
| F04C 2/12        | 2-Punkt Untergruppe | . . of other than internal-axis type [3, 2006.01]   |
| F04C 2/14        | 3-Punkt Untergruppe | . . . with toothed rotary pistons [3, 2006.01]  |
| F04C 2/16        | 4-Punkt Untergruppe | . . . . with helical teeth, e.g. chevron-shaped, screw type [3, 2006.01]  |
| F04C 2/18        | 4-Punkt Untergruppe | . . . . with similar tooth forms (F04C 2/16 takes precedence) [3, 2006.01]  |
| F04C 2/20        | 4-Punkt Untergruppe | . . . . with dissimilar tooth forms (F04C 2/16 takes precedence) [3, 2006.01]   |
| F04C 2/22        | 1-Punkt Untergruppe | . of internal-axis type with equidirectional movement of co-operating members at the points of engagement, or with one of the co-operating members being stationary, the inner member having more teeth or tooth-equivalents than the outer member [3, 2006.01]   |
| F04C 2/24        | 1-Punkt Untergruppe | . of counter-engagement type, i.e. the movement of co-operating members at the points of engagement being in opposite directions [3, 2006.01]   |
| F04C 2/26        | 2-Punkt Untergruppe | . . of internal-axis type [3, 2006.01]  |

| Symbol            | Typ                 | Titel   |
|-------------------|---------------------|---|
| F04C 2/28         | 2-Punkt Untergruppe | . . of other than internal-axis type [3, 2006.01]   |
| F04C 2/30         | 1-Punkt Untergruppe | . having the characteristics covered by two or more of groups F04C 2/02, F04C 2/08, F04C 2/22, F04C 2/24 or having the characteristics covered by one of these groups together with some other type of movement between co-operating members [3, 2006.01]   |
| F04C 2/32         | 2-Punkt Untergruppe | . . having both the movement defined in group F04C 2/02 and relative reciprocation between the co-operating members [3, 2006.01]  |
| F04C 2/324        | 3-Punkt Untergruppe | . . . with vanes hinged to the inner member and reciprocating with respect to the outer member [3, 2006.01]   |
| F04C 2/328        | 4-Punkt Untergruppe | . . . . and hinged to the outer member [3, 2006.01]   |
| F04C 2/332        | 3-Punkt Untergruppe | . . . with vanes hinged to the outer member and reciprocating with respect to the inner member [3, 2006.01]   |
| F04C 2/336        | 4-Punkt Untergruppe | . . . . and hinged to the inner member [3, 2006.01]   |
| F04C 2/34         | 2-Punkt Untergruppe | . . having the movement defined in group F04C 2/08 or F04C 2/22 and relative reciprocation between the co-operating members [3, 2006.01]  |
| F04C 2/344        | 3-Punkt Untergruppe | . . . with vanes reciprocating with respect to the inner member [3, 2006.01]  |
| F04C 2/348        | 4-Punkt Untergruppe | . . . . the vanes positively engaging, with circumferential play, an outer rotatable member [3, 2006.01]  |
| F04C 2/352        | 4-Punkt Untergruppe | . . . . the vanes being pivoted on the axis of the outer member [3, 2006.01]  |
| F04C 2/356        | 3-Punkt Untergruppe | . . . with vanes reciprocating with respect to the outer member [3, 2006.01]  |
| F04C 2/36         | 2-Punkt Untergruppe | . . having both the movements defined in groups F04C 2/22 and F04C 2/24 [3, 2006.01]  |
| F04C 2/38         | 2-Punkt Untergruppe | . . having the movement defined in group F04C 2/02 and having a hinged member (F04C 2/32 takes precedence) [3, 2006.01]   |
| F04C 2/39         | 3-Punkt Untergruppe | . . . with vanes hinged to the inner as well as to the outer member [3, 2006.01]  |
| F04C 2/40         | 2-Punkt Untergruppe | . . having the movement defined in group F04C 2/08 or F04C 2/22 and having a hinged member [3, 2006.01]   |
| F04C 2/44         | 3-Punkt Untergruppe | . . . with vanes hinged to the inner member [3, 2006.01]  |
| F04C 2/46         | 3-Punkt Untergruppe | . . . with vanes hinged to the outer member [3, 2006.01]  |
| <b>F04C 3/00</b>  | <b>Hauptgruppe</b>  | <b>Rotary-piston machines or pumps, with non-parallel axes of movement of co-operating members, e.g. of screw type (with the working-chamber walls at least partly resiliently deformable F04C 5/00; rotary-piston pumps with non-parallel axes of movement of co-operating members specially adapted for elastic fluids F04C 18/48) [1, 2006.01]</b> |
| F04C 3/02         | 1-Punkt Untergruppe | . the axes being arranged at an angle of 90 degrees [5, 2006.01]  |
| F04C 3/04         | 2-Punkt Untergruppe | . . of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing [5, 2006.01]   |
| F04C 3/06         | 1-Punkt Untergruppe | . the axes being arranged otherwise than at an angle of 90 degrees [5, 2006.01]   |
| F04C 3/08         | 2-Punkt Untergruppe | . . of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing [5, 2006.01]   |
| <b>F04C 5/00</b>  | <b>Hauptgruppe</b>  | <b>Rotary-piston machines or pumps with the working-chamber walls at least partly resiliently deformable (such pumps specially adapted for elastic fluids F04C 18/00) [1, 2006.01]</b>  |
| <b>F04C 7/00</b>  | <b>Hauptgruppe</b>  | <b>Rotary-piston machines or pumps with fluid ring or the like (such pumps specially adapted for elastic fluids F04C 19/00) [1, 2006.01]</b>  |
| <b>F04C 9/00</b>  | <b>Hauptgruppe</b>  | <b>Oscillating-piston machines or pumps (such pumps specially adapted for elastic fluids F04C 21/00) [1, 2006.01]</b>   |
| <b>F04C 11/00</b> | <b>Hauptgruppe</b>  | <b>Combinations of two or more machines or pumps, each being of rotary-piston or oscillating-piston type (combinations of such pumps specially adapted for elastic fluids F04C 23/00); Pumping</b>  |

| Symbol            | Typ                 | Titel  |
|-------------------|---------------------|--|
|                   |                     | <b>installations (F04C 13/00 takes precedence; specially adapted for elastic fluids F04C 23/00; fluid gearing F16H 39/00-F16H 47/00) [1, 2006.01]</b>  |
| <b>F04C 13/00</b> | <b>Hauptgruppe</b>  | <b>Adaptations of machines or pumps for special use, e.g. for extremely high pressures (of pumps specially adapted for elastic fluids F04C 25/00) [1, 2006.01]</b>   |
| <b>F04C 14/00</b> | <b>Hauptgruppe</b>  | <b>Control of, monitoring of, or safety arrangements for, machines, pumps or pumping installations (of pumps or pumping installations specially adapted for elastic fluids F04C 28/00) [2006.01]</b>                                     |
| F04C 14/02        | 1-Punkt Untergruppe | . specially adapted for several machines or pumps connected in series or in parallel [2006.01]   |
| F04C 14/04        | 1-Punkt Untergruppe | . specially adapted for reversible machines or pumps [2006.01]   |
| F04C 14/06        | 1-Punkt Untergruppe | . specially adapted for stopping, starting, idling or no-load operation [2006.01]  |
| F04C 14/08        | 1-Punkt Untergruppe | . characterised by varying the rotational speed [2006.01]  |
| F04C 14/10        | 1-Punkt Untergruppe | . characterised by changing the positions of the inlet or outlet openings with respect to the working chamber [2006.01]  |
| F04C 14/12        | 2-Punkt Untergruppe | . . using sliding valves [2006.01]   |
| F04C 14/14        | 2-Punkt Untergruppe | . . using rotating valves [2006.01]  |
| F04C 14/16        | 2-Punkt Untergruppe | . . using lift valves [2006.01]  |
| F04C 14/18        | 1-Punkt Untergruppe | . characterised by varying the volume of the working chamber (by changing the positions of inlet or outlet openings F04C 14/10) [2006.01]  |
| F04C 14/20        | 2-Punkt Untergruppe | . . by changing the form of the inner or outer contour of the working chamber [2006.01]  |
| F04C 14/22        | 2-Punkt Untergruppe | . . by changing the eccentricity between cooperating members [2006.01]   |
| F04C 14/24        | 1-Punkt Untergruppe | . characterised by using valves controlling pressure or flow rate, e.g. discharge valves (F04C 14/10 takes precedence) [2006.01]   |
| F04C 14/26        | 2-Punkt Untergruppe | . . using bypass channels [2006.01]  |
| F04C 14/28        | 1-Punkt Untergruppe | . Safety arrangements; Monitoring [2006.01]  |
| <b>F04C 15/00</b> | <b>Hauptgruppe</b>  | <b>Component parts, details or accessories of machines, pumps or pumping installations, not provided for in groups F04C 2/00-F04C 14/00 (of pumps specially adapted for elastic fluids F04C 18/00-F04C 29/00) [1, 2006.01]</b>           |
| F04C 15/06        | 1-Punkt Untergruppe | . Arrangements for admission or discharge of the working fluid, e.g. constructional features of the inlet or outlet [2006.01]  |
|                   |                     | <b><u>Pumps specially adapted for elastic fluids</u></b>   |
| <b>F04C 18/00</b> | <b>Hauptgruppe</b>  | <b>Rotary-piston pumps specially adapted for elastic fluids (with fluid ring or the like F04C 19/00; rotary-piston pumps in which the working-fluid is exclusively displaced by one or more reciprocating pistons F04B) [3, 2006.01]</b> |
| F04C 18/02        | 1-Punkt Untergruppe | . of arcuate-engagement type, i.e. with circular translatory movement of co-operating members, each member having the same number of teeth or tooth-equivalents [3, 2006.01]   |
| F04C 18/04        | 2-Punkt Untergruppe | . . of internal-axis type [3, 2006.01]   |
| F04C 18/06        | 2-Punkt Untergruppe | . . of other than internal-axis type (F04C 18/063 takes precedence) [3, 2006.01]   |
| F04C 18/063       | 2-Punkt Untergruppe | . . with coaxially-mounted members having continuously-changing circumferential spacing between them [3, 2006.01]  |
| F04C 18/067       | 3-Punkt Untergruppe | . . . having cam-and-follower type drive [3, 2006.01]  |
| F04C 18/07        | 3-Punkt Untergruppe | . . . having crankshaft-and-connecting-rod type drive [3, 2006.01]   |
| F04C 18/073       | 3-Punkt Untergruppe | . . . having pawl-and-ratchet type drive [3, 2006.01]  |

| Symbol      | Typ                 | Titel  |
|-------------|---------------------|--|
| F04C 18/077 | 3-Punkt Untergruppe | . . . having toothed-gearing type drive [3, 2006.01]   |
| F04C 18/08  | 1-Punkt Untergruppe | . of intermeshing-engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing [3, 2006.01]  |
| F04C 18/10  | 2-Punkt Untergruppe | . . of internal-axis type with the outer member having more teeth or tooth-equivalents, e.g. rollers, than the inner member [3, 2006.01]   |
| F04C 18/107 | 3-Punkt Untergruppe | . . . with helical teeth [3, 2006.01]  |
| F04C 18/113 | 3-Punkt Untergruppe | . . . the inner member carrying rollers intermeshing with the outer member [3, 2006.01]  |
| F04C 18/12  | 2-Punkt Untergruppe | . . of other than internal-axis type [3, 2006.01]  |
| F04C 18/14  | 3-Punkt Untergruppe | . . . with toothed rotary pistons [3, 2006.01]   |
| F04C 18/16  | 4-Punkt Untergruppe | . . . . with helical teeth, e.g. chevron-shaped, screw type [3, 2006.01]   |
| F04C 18/18  | 4-Punkt Untergruppe | . . . . with similar tooth forms (F04C 18/16 takes precedence) [3, 2006.01]  |
| F04C 18/20  | 4-Punkt Untergruppe | . . . . with dissimilar tooth forms (F04C 18/16 takes precedence) [3, 2006.01]   |
| F04C 18/22  | 1-Punkt Untergruppe | . of internal-axis type with equidirectional movement of co-operating members at the points of engagement, or with one of the co-operating members being stationary, the inner member having more teeth or tooth-equivalents than the outer member [3, 2006.01]            |
| F04C 18/24  | 1-Punkt Untergruppe | . of counter-engagement type, i.e. the movement of co-operating members at the points of engagement being in opposite directions [3, 2006.01]  |
| F04C 18/26  | 2-Punkt Untergruppe | . . of internal-axis type [3, 2006.01]   |
| F04C 18/28  | 2-Punkt Untergruppe | . . of other than internal-axis type [3, 2006.01]  |
| F04C 18/30  | 1-Punkt Untergruppe | . having the characteristics covered by two or more of groups F04C 18/02, F04C 18/08, F04C 18/22, F04C 18/24, F04C 18/48, or having the characteristics covered by one of these groups together with some other type of movement between co-operating members [3, 2006.01] |
| F04C 18/32  | 2-Punkt Untergruppe | . . having both the movement defined in group F04C 18/02 and relative reciprocation between the co-operating members [3, 2006.01]  |
| F04C 18/324 | 3-Punkt Untergruppe | . . . with vanes hinged to the inner member and reciprocating with respect to the outer member [3, 2006.01]  |
| F04C 18/328 | 4-Punkt Untergruppe | . . . . and hinged to the outer member [3, 2006.01]  |
| F04C 18/332 | 3-Punkt Untergruppe | . . . with vanes hinged to the outer member and reciprocating with respect to the inner member [3, 2006.01]  |
| F04C 18/336 | 4-Punkt Untergruppe | . . . . and hinged to the inner member [3, 2006.01]  |
| F04C 18/34  | 2-Punkt Untergruppe | . . having the movement defined in group F04C 18/08 or F04C 18/22 and relative reciprocation between the co-operating members [3, 2006.01]   |
| F04C 18/344 | 3-Punkt Untergruppe | . . . with vanes reciprocating with respect to the inner member [3, 2006.01]   |
| F04C 18/348 | 4-Punkt Untergruppe | . . . . the vanes positively engaging, with circumferential play, an outer rotatable member [3, 2006.01]   |
| F04C 18/352 | 4-Punkt Untergruppe | . . . . the vanes being pivoted on the axis of the outer member [3, 2006.01]   |
| F04C 18/356 | 3-Punkt Untergruppe | . . . with vanes reciprocating with respect to the outer member [3, 2006.01]   |
| F04C 18/36  | 2-Punkt Untergruppe | . . having both the movements defined in groups F04C 18/22 and F04C 18/24 [3, 2006.01]   |
| F04C 18/38  | 2-Punkt Untergruppe | . . having the movement defined in group F04C 18/02 and having a hinged member (F04C 18/32 takes precedence) [3, 2006.01]  |

| Symbol            | Typ                 | Titel   |
|-------------------|---------------------|---|
| F04C 18/39        | 3-Punkt Untergruppe | . . . with vanes hinged to the inner as well as to the outer member [3, 2006.01]  |
| F04C 18/40        | 2-Punkt Untergruppe | . . having the movement defined in group F04C 18/08 or F04C 18/22 and having a hinged member [3, 2006.01]   |
| F04C 18/44        | 3-Punkt Untergruppe | . . . with vanes hinged to the inner member [3, 2006.01]  |
| F04C 18/46        | 3-Punkt Untergruppe | . . . with vanes hinged to the outer member [3, 2006.01]  |
| F04C 18/48        | 1-Punkt Untergruppe | . Rotary-piston pumps with non-parallel axes of movement of co-operating members [5, 2006.01]   |
| F04C 18/50        | 2-Punkt Untergruppe | . . the axes being arranged at an angle of 90 degrees [5, 2006.01]  |
| F04C 18/52        | 3-Punkt Untergruppe | . . . of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing [5, 2006.01]   |
| F04C 18/54        | 2-Punkt Untergruppe | . . the axes being arranged otherwise than at an angle of 90 degrees [5, 2006.01]   |
| F04C 18/56        | 3-Punkt Untergruppe | . . . of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing [5, 2006.01]   |
| <b>F04C 19/00</b> | <b>Hauptgruppe</b>  | <b>Rotary-piston pumps with fluid ring or the like, specially adapted for elastic fluids [1, 2006.01]</b>   |
| <b>F04C 21/00</b> | <b>Hauptgruppe</b>  | <b>Oscillating-piston pumps specially adapted for elastic fluids [1, 2006.01]</b>   |
| <b>F04C 23/00</b> | <b>Hauptgruppe</b>  | <b>Combinations of two or more pumps, each being of rotary-piston or oscillating-piston type, specially adapted for elastic fluids; Pumping installations specially adapted for elastic fluids; Multi-stage pumps specially adapted for elastic fluids (F04C 25/00 takes precedence) [1, 2006.01]</b> |
| F04C 23/02        | 1-Punkt Untergruppe | . Pumps characterised by combination with, or adaptation to, specific driving engines or motors (predominant aspects of the engines or motors, <u>see</u> the relevant classes) [1, 2006.01]  |
| <b>F04C 25/00</b> | <b>Hauptgruppe</b>  | <b>Adaptations for special use of pumps for elastic fluids [1, 2006.01]</b>   |
| F04C 25/02        | 1-Punkt Untergruppe | . for producing high vacuum (sealing arrangements F04C 27/00; silencing F04C 29/06) [1, 2006.01]  |
| <b>F04C 27/00</b> | <b>Hauptgruppe</b>  | <b>Sealing arrangements in rotary-piston pumps specially adapted for elastic fluids [1, 2006.01]</b>  |
| F04C 27/02        | 1-Punkt Untergruppe | . Liquid sealing for high-vacuum pumps [1, 2006.01]   |
| <b>F04C 28/00</b> | <b>Hauptgruppe</b>  | <b>Control of, monitoring of, or safety arrangements for, pumps or pumping installations specially adapted for elastic fluids [2006.01]</b>   |
| F04C 28/02        | 1-Punkt Untergruppe | . specially adapted for several pumps connected in series or in parallel [2006.01]  |
| F04C 28/04        | 1-Punkt Untergruppe | . specially adapted for reversible pumps [2006.01]  |
| F04C 28/06        | 1-Punkt Untergruppe | . specially adapted for stopping, starting, idling or no-load operation [2006.01]   |
| F04C 28/08        | 1-Punkt Untergruppe | . characterised by varying the rotational speed [2006.01]   |
| F04C 28/10        | 1-Punkt Untergruppe | . characterised by changing the positions of the inlet or outlet openings with respect to the working chamber [2006.01]   |
| F04C 28/12        | 2-Punkt Untergruppe | . . using sliding valves [2006.01]  |
| F04C 28/14        | 2-Punkt Untergruppe | . . using rotating valves [2006.01]   |
| F04C 28/16        | 2-Punkt Untergruppe | . . using lift valves [2006.01]   |
| F04C 28/18        | 1-Punkt Untergruppe | . characterised by varying the volume of the working chamber (by changing the positions of inlet or outlet openings F04C 28/10) [2006.01]   |
| F04C 28/20        | 2-Punkt Untergruppe | . . by changing the form of the inner or outer contour of the working chamber [2006.01]   |
| F04C 28/22        | 2-Punkt Untergruppe | . . by changing the eccentricity between cooperating members [2006.01]  |

| Symbol            | Typ                 | Titel  |
|-------------------|---------------------|--|
| F04C 28/24        | 1-Punkt Untergruppe | . characterised by using valves controlling pressure or flow rate, e.g. discharge valves (F04C 28/10 takes precedence) [2006.01]   |
| F04C 28/26        | 2-Punkt Untergruppe | . . using bypass channels [2006.01]  |
| F04C 28/28        | 1-Punkt Untergruppe | . Safety arrangements; Monitoring [2006.01]  |
| <b>F04C 29/00</b> | <b>Hauptgruppe</b>  | <b>Component parts, details, or accessories, of pumps or pumping installations specially adapted for elastic fluids, not provided for in groups F04C 18/00-F04C 28/00 [1, 2006.01]</b> |
| F04C 29/02        | 1-Punkt Untergruppe | . Lubrication; Lubricant separation [1, 2006.01]   |
| F04C 29/04        | 1-Punkt Untergruppe | . Heating; Cooling; Heat insulation [1, 2006.01]   |
| F04C 29/06        | 1-Punkt Untergruppe | . Silencing [1, 2006.01]   |
| F04C 29/12        | 1-Punkt Untergruppe | . Arrangements for admission or discharge of the working fluid, e.g. constructional features of the inlet or outlet [2006.01]  |