

Symbol	Typ	Titel
<b>F</b>	<b>Sektion</b>	<b>MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING</b>
<b>F23</b>	<b>Klasse</b>	<b>COMBUSTION APPARATUS; COMBUSTION PROCESSES</b>
<b>F23C</b>	<b>Unterklasse</b>	<b>METHODS OR APPARATUS FOR COMBUSTION USING FLUID FUEL OR SOLID FUEL SUSPENDED IN AIR (burners F23D)</b>
<b>F23C 1/00</b>	<b>Hauptgruppe</b>	<b>Combustion apparatus specially adapted for combustion of two or more kinds of fuel simultaneously or alternately, at least one kind of fuel being either a fluid fuel or a solid fuel suspended in air (combustion apparatus characterised by the combination of two or more combustion chambers F23C 6/00; pilot flame igniters F23Q 9/00) [1, 7, 2006.01]</b>
F23C 1/02	1-Punkt Untergruppe	. lump and liquid fuel [1, 2006.01]
F23C 1/04	1-Punkt Untergruppe	. lump and gaseous fuel [1, 2006.01]
F23C 1/06	1-Punkt Untergruppe	. lump and pulverulent fuel [1, 2006.01]
F23C 1/08	1-Punkt Untergruppe	. liquid and gaseous fuel [1, 2006.01]
F23C 1/10	1-Punkt Untergruppe	. liquid and pulverulent fuel [1, 2006.01]
F23C 1/12	1-Punkt Untergruppe	. gaseous and pulverulent fuel [1, 2006.01]
<b>F23C 3/00</b>	<b>Hauptgruppe</b>	<b>Combustion apparatus characterised by the shape of the combustion chamber (F23C 15/00 takes precedence) [1, 7, 2006.01]</b>
<b>F23C 5/00</b>	<b>Hauptgruppe</b>	<b>Combustion apparatus characterised by the arrangement or mounting of burners [1, 7, 2006.01]</b>
F23C 5/02	1-Punkt Untergruppe	. Structural details of mounting [1, 2006.01]
F23C 5/06	2-Punkt Untergruppe	. . Provision for adjustment of burner position during operation [1, 2006.01]
F23C 5/08	1-Punkt Untergruppe	. Disposition of burners [1, 2006.01]
F23C 5/14	2-Punkt Untergruppe	. . to obtain a single flame of concentrated or substantially planar form, e.g. pencil or sheet flame (F23C 5/32 takes precedence) [1, 3, 2006.01]
F23C 5/24	2-Punkt Untergruppe	. . to obtain a loop flame [1, 2006.01]
F23C 5/28	2-Punkt Untergruppe	. . to obtain flames in opposing directions, e.g. impacting flames [1, 2006.01]
F23C 5/32	2-Punkt Untergruppe	. . to obtain rotating flames, i.e. flames moving helically or spirally [3, 2006.01]
<b>F23C 6/00</b>	<b>Hauptgruppe</b>	<b>Combustion apparatus characterised by the combination of two or more combustion chambers [3, 7, 2006.01]</b>
F23C 6/02	1-Punkt Untergruppe	. in parallel arrangement [3, 2006.01]
F23C 6/04	1-Punkt Untergruppe	. in series connection [3, 2006.01]
<b>F23C 7/00</b>	<b>Hauptgruppe</b>	<b>Combustion apparatus characterised by arrangements for air supply (inlets for fluidisation air F23C 10/20; baffles or shields with air supply passages F23M 9/04) [1, 7, 2006.01]</b>
F23C 7/02	1-Punkt Untergruppe	. Disposition of air supply not passing through burner [1, 2006.01]
F23C 7/04	2-Punkt Untergruppe	. . to obtain maximum heat transfer to wall of combustion chamber [1, 2006.01]
F23C 7/06	2-Punkt Untergruppe	. . for heating the incoming air (arrangements of regenerators or recuperators F23L 15/00) [1, 2006.01]
F23C 7/08	3-Punkt Untergruppe	. . . indirectly by a secondary fluid other than the combustion products [1, 2006.01]
<b>F23C 9/00</b>	<b>Hauptgruppe</b>	<b>Combustion apparatus characterised by arrangements for returning combustion products or flue gases to the combustion chamber (fluidised bed combustion apparatus with means for recirculation of particles entrained from the bed F23C 10/02; fluidised bed combustion apparatus with devices for removal and partial reintroduction of material from the bed F23C 10/26) [1, 7, 2006.01]</b>

Symbol	Typ	Titel
F23C 9/06	1-Punkt Untergruppe	. for completing combustion [3, 2006.01]
F23C 9/08	1-Punkt Untergruppe	. for reducing temperature in combustion chamber, e.g. for protecting walls of combustion chamber [3, 2006.01]
<b>F23C 10/00</b>	<b>Hauptgruppe</b>	<b>Apparatus in which combustion takes place in a fluidised bed of fuel or other particles [7, 2006.01]</b>
F23C 10/01	1-Punkt Untergruppe	. in a fluidised bed of catalytic particles [2006.01]
F23C 10/02	1-Punkt Untergruppe	. with means specially adapted for achieving or promoting a circulating movement of particles within the bed or for a recirculation of particles entrained from the bed [7, 2006.01]
F23C 10/04	2-Punkt Untergruppe	. . the particles being circulated to a section, e.g. a heat-exchange section or a return duct, at least partially shielded from the combustion zone, before being reintroduced into the combustion zone [7, 2006.01]
F23C 10/06	3-Punkt Untergruppe	. . . the circulating movement being promoted by inducing differing degrees of fluidisation in different parts of the bed [7, 2006.01]
F23C 10/08	3-Punkt Untergruppe	. . . characterised by the arrangement of separation apparatus, e.g. cyclones, for separating particles from the flue gases [7, 2006.01]
F23C 10/10	4-Punkt Untergruppe	. . . . the separation apparatus being located outside the combustion chamber [7, 2006.01]
F23C 10/12	2-Punkt Untergruppe	. . the particles being circulated exclusively within the combustion zone [7, 2006.01]
F23C 10/14	3-Punkt Untergruppe	. . . the circulating movement being promoted by inducing differing degrees of fluidisation in different parts of the bed [7, 2006.01]
F23C 10/16	1-Punkt Untergruppe	. specially adapted for operation at superatmospheric pressures, e.g. by the arrangement of the combustion chamber and its auxiliary systems inside a pressure vessel [7, 2006.01]
F23C 10/18	1-Punkt Untergruppe	. Details; Accessories [7, 2006.01]
F23C 10/20	2-Punkt Untergruppe	. . Inlets for fluidisation air, e.g. grids; Bottoms [7, 2006.01]
F23C 10/22	2-Punkt Untergruppe	. . Fuel feeders specially adapted for fluidised bed combustion apparatus (F23C 10/26 takes precedence) [7, 2006.01]
F23C 10/24	2-Punkt Untergruppe	. . Devices for removal of material from the bed (devices for controlling the level of the bed or the amount of material in the bed F23C 10/30) [7, 2006.01]
F23C 10/26	3-Punkt Untergruppe	. . . combined with devices for partial reintroduction of material into the bed, e.g. after separation of agglomerated parts [7, 2006.01]
F23C 10/28	2-Punkt Untergruppe	. . Control devices specially adapted for fluidised bed combustion apparatus [7, 2006.01]
F23C 10/30	3-Punkt Untergruppe	. . . for controlling the level of the bed or the amount of material in the bed [7, 2006.01]
F23C 10/32	4-Punkt Untergruppe	. . . . by controlling the rate of recirculation of particles separated from the flue gases [7, 2006.01]
<b>F23C 13/00</b>	<b>Hauptgruppe</b>	<b>Apparatus in which combustion takes place in the presence of catalytic material (in a fluidised bed of catalytic particles F23C 10/01; radiant gas burners using catalysis for flameless combustion F23D 14/18) [2006.01]</b>
F23C 13/02	1-Punkt Untergruppe	. characterised by arrangements for starting the operation, e.g. for heating the catalytic material to operating temperature [2006.01]
F23C 13/04	1-Punkt Untergruppe	. characterised by the arrangement of two or more catalytic elements in series connection [2006.01]
F23C 13/06	1-Punkt Untergruppe	. in which non-catalytic combustion takes place in addition to catalytic combustion, e.g. downstream of a catalytic element [2006.01]
F23C 13/08	1-Punkt Untergruppe	. characterised by the catalytic material [2006.01]
<b>F23C 15/00</b>	<b>Hauptgruppe</b>	<b>Apparatus in which combustion takes place in pulses influenced by acoustic resonance in a gas</b>

Symbol	Typ	Titel
		<b>mass [2006.01]</b>
<b>F23C 99/00</b>	<b>Hauptgruppe</b>	<b>Subject matter not provided for in other groups of this subclass [2006.01]</b> <b><u>Indexing scheme associated with group F23C 10/00, relating to combustion in entrained fluidised beds. [7]</u></b>
<b>F23C 101/00</b>	<b>Hauptgruppe</b>	<b>Combustion in entrained fluidised beds, i.e. fluidised beds which have no distinct upper surface [7, 2006.01]</b>